

Z5750

1.0 gpf Washout Urinal

Z5750 Series

- 1.0 gpf [3.8 Lpf]
- Vitreous china
- Washout flushing action
- 3/4" top spud
- 2" I.P.S. outlet flange and rubber gasket with integral trap
- 14" extended rim for handicap compliance when installed at proper height
- Shipping Weight: 65 lbs.

Engineering Specification

- Z5750 with Top Spud**
Vitreous china, 1.0 gpf [3.8 Lpf] low consumption, wall hung urinal with 3/4" top spud and concealed wall hanger brackets.

Recommended Trim

- Z6003AV-WS1** AquaVantage® AV low consumption exposed urinal flush valve.
- Z5978-STR** Urinal Dome Strainer

Optional Water-Savings Trim

- Z6003AV-EWS** AquaVantage® AV .5 gpf extra water savings exposed urinal flush valve.



Z5750 Series 1.0 gpf washout urinal shown with Z6003AV-WS1 flush valve (sold separately).

See Z5798 for EcoVantage™ 1/8 gallon of water per flush urinal system.

Fixtures meet ASME A112.19.2 and CSA B45 standard requirements.

 Meets the American Disabilities Guidelines and ANSI A117.1 requirements when urinal is installed 17" [432mm] from finished floor.

See Zurn One Systems for suggested packages.

This Space is for Architectural/Engineering Approval